
PERFORMANCE UNDER PRESSURE



NEO SYNTHETIC LO VIS MVP ATF

Product Description

NEO SYNTHETIC Lo Vis MVP ATF is manufactured to meet Multi Vehicle OEM specifications from premium quality synthetic base oils blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter.

NEO SYNTHETIC Lo Vis MVP ATF is a multi-purpose fluid that meets and exceeds current original equipment manufacturers specifications for automatic transmission fluids, including some of the latest OEM specifications as specified by GM, Ford, Chrysler, Toyota, Mitsubishi and others.

Product Performances

- AUDI / VW[®] G-055-005-A2
- GM: D VI** (backward compatible to DII/III/IIIG/IIIIH)
- FORD: M-LV, M-SP
- HYUNDAI / KIA: SP-IV
- MITSUBISHI: Diaqueen ATF J-3
- MERCEDES BENZ: MB 236.12
- NISSAN MATIC S (backward compatible to Matic D / Matic J)
- SAAB: 93 165 147
- TOYOTA / LEXUS / SCION: WS
- OEMs: M 1375.4

Features

- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability compared to conventional ATF Fluids.
- Protects against rust and corrosion.
- Outstanding seal compatibility.
- Will not degrade nylon components.
- Dyed red to detect leaks.
- Multi-functional Low viscosity ATF fluid – Reduced inventory.

Note: *Not recommended where ever CVT fluids or Type F or Power Steering Fluids for **Honda** are specified.*

**** Suitable for use, based on same technology data.**

Test

Gravity, ° API	30.5
Pour Point, ° F	-50
Viscosity Index	> 145
Viscosity @ 100°C. cSt	6.0 – 6.2
Viscosity @ -40°C. cP Brookfield	7,900
Color, D-1500	Red

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY